



Main Application :

Mainly used for Automatic Curtains, Stage Lights, Electric Advertisement, Electric Appliances, Pumps, Scientific & Teaching Devices, etc which needs high torque but low speed.

Standard Performances (Test Under Room Temperature) :

Model	Ph.	Rated Volt.	Rated Freq'y	Output Speed	Input Current	Input Power	Max. Torque	Rated Torque	Start Torque	Capacitor	Motor Length	G.W.
		(VAC)	(Hz)	(rpm)	(A)	(W)	(Nm)	(Nm)	(Nm)	(μ F/V)	(mm)	(Kgs)
NSR90-060-6L	1	220	50	60	0.20	40	2.00	1.90	0.95	2.7/400	85	2.4
NSR90-060-6	1	220	50	60	0.35	70	2.80	2.60	1.35	4.0/400	100	3.2
NSR90-060	1	220	50	60	0.35	70	3.00	2.80	1.40	2.7/400	100	3.2
NSR90-060-2	3	220	50	60	0.30	60	3.80	3.55	1.80		100	3.2
NSR90-060-3	3	380	50	60	0.18	60	3.80	3.55	1.80		100	3.2
NSR90-060-H	1	220	50	60	0.50	90	3.50	3.30	1.65	3.0/400	120	4.0
NSR90-115-L	1	220	50	115	0.20	40	1.60	1.45	0.80	2.7/400	85	2.4
NSR90-115-6	1	220	50	115	0.35	70	2.20	2.00	1.05	4.0/400	100	3.2
NSR90-115	1	220	50	115	0.40	80	2.55	2.30	1.05	2.7/400	100	3.2
NSR90-115-2	3	220	50	115	0.40	80	3.30	3.00	1.60		100	3.2
NSR90-115-3	3	380	50	115	0.22	80	3.30	3.00	1.60		100	3.2
NSR90-115-H	1	220	50	115	0.50	90	3.10	2.80	1.50	4.0/400	120	4.0
NSR90-136	1	220	50	136	0.40	80	2.40	2.20	1.10	2.7/400	100	3.2
NSR90-136-2	3	220	50	136	0.40	80	3.00	2.70	1.50		100	3.2
NSR90-136-3	3	380	50	136	0.23	80	3.00	2.70	1.50		100	3.2

Remarks: The voltage can be changed to any as needed. The torque @ 50Hz is 1.2 times of the torque @ 60Hz.
All above performances are from some typical models only. OEM and ODM are all welcome.

NOSTOP MOTOR GROUP HEAD OFFICE:

BUILDING C#, GANGZHILONG SCIENCE & TECH. INDUS. PARK, HEPING EAST RD., LONGHUA TOWN, SHENZHEN, P.R.CHINA
TEL: (+86.755) 2967 4819, 2967 4809, 2967 4212, 2967 4862, 2983 4766 FAX: (+86.755) 2967 4299
URL: <http://www.nostop.cn>, <http://www.nostopmotor.com> E-mail: stony@nostop.cn Postal Code: 518107